



16- channel surge protection to UTP and coaxial cable with power supply distribution


LHD-16R-PRO-FPS

LHD-16R-PRO-FPS is rack mount system designed to protect CCTV instalations from lightnings, electrostatic overvoltages and vandalism.

LHD series is universal for UTP twisted pair and coaxial cable. You can choose which one will be connected by switching jumpers on PCB (Coaxial / UTP).

The device include high quality converter (transformer), change impedance UTP to coaxial cable. The device dedicated is to transmission signal high frequency, which using to transmission Video HD in systems AHD, HD-CVI, HD-TVI / Turbo HD.

Built-in camera **power distributor FPS** - provides 16 independents power outputs, protects from short circuit and lightnings. It is equipped on optical signal of power supply to each channels and buzzer signaling of short circuit on any of them.



Specification:	
Video channel	16
Impedance UTP	75 Ohm
Impedance BNC	100 Ohm
Connector input (line)	Socket screw/ UTP
Connector output (device)	Wire with male BNC
Frequency response	42 MHz
Tłumienie	0.4dB
Protect	3 - Air ionizing, gas tube, transcient bridge
Protect line-ground	Gas tube: 90V, 2x10kA @ 8/20uS
Protect line-line	Transcient bridge: 6V, 100A @ 8/20uS
Maximum level overvoltage	4kV
Capacity circuit	Maximum 7~9pF
Power supply channel	16
Input socket	Connector DC
Output socket	Screw connection
Nominal voltage	12V
Protection	Overvoltage, overload, short circuit
Dimension	1U rack 19"

EWIMAR Sp. z o. o.
ul. Konarskiego 84
01-355 Warszawa

Export sales
e-mail: export@ewimar.pl
tel. + 48 22 691 90 65